



## Industrial Enamel Spray Primer



### Product Description

A fast drying surface sealer that provides maximum rust protection and better adhesion for the topcoat.

### Features

- Professional grade
- Ultimate protection
- Superior adhesion

### Typical Properties (*80000 Series*)

#### Dry Time:

**To the touch:** 30-50 minute(s)

**Recoat:** Within 2 hour(s) or after 48 hour(s)

#### Surface Coverage:

Coverage varies depending on surface color and porosity.

### Colors and Part Numbers

	Part Numbers
Gray	80012
Red Oxide	80013

### Recommended Uses

- Metal
- Wood
- Concrete
- Masonry

### Can Size and Fill Weight

**Can Size:** 20 oz.

**Fill Weight:** 15 oz.

## Application Instructions

Read the Lead Warning in Cautions section. Use with a primer for additional rust prevention.

**Directions:** USE WITH ADEQUATE VENTILATION.

1. Clean and dry surface. Remove dirt, grease, etc.
2. Use outdoors or in a well-ventilated area when temperature is 65–90 °F (18–32 °C).
3. Protect surrounded areas from spray mist.
4. Shake can for at least 1 minute after rattle of mixing ball is heard. Shake frequently during application.
5. Spray surface with steady even strokes at a distance of 8-10 inches (20-25 cm) from surface. Several light coats give a better finish than one heavy coat. Overlap each stroke. Two (2) thin coats are recommended.
6. If spray button clogs, remove button from can and run knife-edge through slit at the end of the spray button stem. DO NOT insert pins or other sharp objects into valve opening of can.
7. To clear spray button for future use, turn can upside down and spray for 3 seconds. Dispose of cans responsibly. DO NOT incinerate or compact.

## Cautions (8000 Series)

**CONTAINS: DIMETHYL KETONE, PETROLEUM DISTILLATES, ISOBUTYL ACETATE, XYLENE, ETHYLBENZENE.**

**WARNING: EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE. CONTENTS UNDER PRESSURE. Vapor Harmful.** May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120 °F (49 °C). Replace cap after each use. **Vapors may ignite explosively.** Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build up of vapors by opening all windows and doors to achieve cross-ventilation. **Use only with adequate ventilation.** Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothes.

**Warning:** This product contains chemicals known to the State of California to cause cancer.

**FIRST AID:** EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** IF INHALED: If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** IF SWALLOWED: Drink 2 glasses of water. **Get medical attention immediately.**

**Delayed effect from long term exposure:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**DO NOT TAKE INTERNALLY.  
KEEP OUT OF REACH OF CHILDREN.  
For additional safety and chronic health hazard  
information, refer to the Material Safety Data  
Sheet for this product.**

**EMERGENCY MEDICAL TELEPHONE:  
1-888-345-5732**

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean-up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product, is the replacement of the defective product, or a refund of its purchase price, at our option.