



## All Purpose Enamel Spray Primer



### Product Description

Use a primer on interior or exterior projects to improve top coat adhesion and enhance final appearance.

### Features

- Interior/Exterior
- For wood, metal and more
- Weather resistant
- Resistant against corrosion, chemicals, gasoline and UV light

### Colors Information

	Part Number
Red Oxide	81016
Gray Primer	81009

### Typical Properties (*81000 Series*)

#### Dry Time:

**To the touch:** 20-30 minute(s)

**Recoat:** Within 1 hour or after 24 hour(s)

#### Surface Coverage:

Coverage varies depending on surface color and porosity.

### Recommended Uses

- Metal
- Wood

### Can Size and Fill Weight

**Can Size:** 16 oz.

**Fill Weight:** 12 fl. oz.

## Application Instructions

Read the Lead Warning in Cautions section. USE WITH ADEQUATE VENTILATION.

1. Clean and dry surface. Remove dirt, grease, etc. Dull glossy surfaces. Prime bare metal.
2. Use outdoors or in a well-ventilated area where temperature is 65–90 °F (18–32 °C).
3. Cover nearby area to protect from spray mist.
4. Shake well for at least 1 minute, listening for rattle of mixing ball. Shake frequently during application.
5. Hold the can 8-10 inches from surface. Move can back and forth, releasing button after each stroke. Overlap each stroke. Two (2) thin coats are recommended. Recoat within 1 hour or after 24 hours, otherwise paint may wrinkle or lift. Dry to handle in 1 hour.
6. If spray button clogs, remove button from can and run knife-edge through slit at end of spray button stem. DO NOT insert pins or other sharp objects into valve opening of can.
7. To prevent clogging after use, turn can upside down and press spray head for 3 seconds.

## Cautions (81000 Series)

**CONTAINS NO CFC's** – in accordance with Federal regulations which prohibit the use of CFC propellants in aerosols. **CONTAINS ACETONE, MINERAL SPIRITS, XYLENE, ISOBUTYL ACETATE AND ETHYLBENZENE.**

**WARNING: Vapor Harmful.** May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120 °F (49 °C). Replace cap after each use. **Vapors may ignite explosively.** Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build up of vapors by opening all windows and doors to achieve cross-ventilation. **Use only with adequate ventilation.** Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothes.

**Warning:** This product contains chemicals known to the State of California to cause cancer.

**FIRST AID: EYE CONTACT:** Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** **IF SWALLOWED:** Drink 2 glasses of water. **Get medical attention immediately.**

**Delayed effect from long-term exposure:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**DO NOT TAKE INTERNALLY.  
KEEP OUT OF REACH OF CHILDREN.  
For additional safety and chronic health hazard  
information, refer to the Material Safety Data  
Sheet for this product.**

**EMERGENCY MEDICAL TELEPHONE:  
1-888-345-5732**

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean-up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product, is the replacement of the defective product, or a refund of its purchase price, at our option.